

## Technical Data Sheet

93800051112\_V01\_en\_GB

Voltage / Frequency

Cooling water temperature (in / out)

NOx emissions (dry, 5 % O<sub>2</sub>)

Mixture cooler 1st stage water temperature (in)

Mixture cooler 2nd stage water temperature (in)

Exhaust gas temperature

Catalytic converter

Special equipment

Altitude above sea level

Combustion air temperature

Relative combustion air humidity

Standard specifications and regulations

## MTU 8V4000 GS

GG08V4000A1



V / Hz	400	/	50
°C		78 / 90	
mg/m <sup>3</sup> i.N.		< 250	
°C			
°C		43	
°C		423	
		not included	
m / mbar	100	/	1000
°C		25	
%		30	

### Energy balance

	%	100	75	50
Electrical Power <sup>2) 3)</sup>	kW	1013	760	507
Energy input <sup>4) 5)</sup>	kW	2423	1839	1292
Thermal output total <sup>6)</sup>	kW	517	376	254
Thermal output engine (block, lube oil, 1st stage mixture cooler) <sup>6)</sup>	kW	517	376	254
Thermal output mixture cooler 1st stage <sup>6)</sup>	kW			
Thermal output mixture cooler 2nd stage <sup>6)</sup>	kW	74	50	32
Exhaust heat ( 120 °C ) <sup>6)</sup>	kW	( 509 )	( 427 )	( 331 )
Engine power ISO 3046-1 <sup>2)</sup>	kW	1040	783	526
Generator efficiency at power factor = 1	%	97.4	97.1	96.4
Electrical efficiency <sup>4)</sup>	%	41.8	41.3	39.2
Total efficiency	%	84.2	85.0	84.5
Power consumption <sup>7)</sup>	kW			

### Combustion air / Exhaust gas

Combustion air volume flow <sup>1)</sup>	m <sup>3</sup> i.N./h	4113	3059	2097
Combustion air mass flow	kg/h	5311	3950	2708
Exhaust gas volume flow, wet <sup>1)</sup>	m <sup>3</sup> i.N./h	4250	3163	2168
Exhaust gas volume flow, dry <sup>1)</sup>	m <sup>3</sup> i.N./h	3936	2924	2001
Exhaust gas mass flow, wet	kg/h	5494	4089	2804
Exhaust temperature after turbocharger	°C	423	459	502

### Reference fuel <sup>8)</sup>

Natural gas	CH <sub>4</sub> > 95 Vol.%
Sewage gas	not applicable
Biogas	not applicable
Landfill gas	not applicable

### Fuel requirements <sup>9)</sup>

Minimum methane number	MN	80
Range of heating value: design / operation range without power derating	kWh/m <sup>3</sup> i.N.	10.0 - 10.5 / 8.0 - 11.0

### Exhaust gas emissions <sup>9) 8)</sup>

NOx, stated as NO <sub>2</sub> (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	< 250
CO (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	< 1000
HCHO (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	
VOC (dry, 5 % O <sub>2</sub> )	mg/m <sup>3</sup> i.N.	

### Otto-gas engine, lean burn operation with turbocharging

Number of cylinders / configuration	8	/	V
Engine type			8V4000L64
Engine speed	1/min		1500
Bore	mm		170.0
Stroke	mm		210.0
Displacement	dm <sup>3</sup>		38.1
Mean piston speed	m/s		10.5
Compression ratio			14.0
BMEP at nominal engine speed min-1	bar	21.8	
Lube oil consumption <sup>10)</sup>	dm <sup>3</sup> /h	0.18	
Exhaust back pressure min. - max. after module	mbar - mbar		30 - 60

### Generator

Rating power (temperature rise class F) <sup>11)</sup>	kVA	1770
Insulation class / temperature rise class		F / F
Winding pitch		2/3
Protection		IP 23
Max. allowable p.f. inductive (overexcited) / capacitive (underexcited) <sup>12)</sup>		0.8 / 0.95
Voltage tolerance / frequency tolerance	%	± 10 / ± 5

### Engine cooling water system

Coolant temperature (in / out), design	°C	78 / 90
Coolant flow rate, constant <sup>13) 14)</sup>	m <sup>3</sup> /h	40.1

Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m <sup>3</sup> /h	1.75	/	30.8
--------------------------------------	-----------------------------	-------------------------	------	---	------

Max. operation pressure (coolant before engine)	bar		6.0
---	-----	--	-----

### Exhaust gas heat exchanger (EGHE)

Exhaust gas temperature (out)	°C	
Coolant temperature (in / out), design	°C	
Coolant volumetric flow, constant <sup>13) 14)</sup>	m <sup>3</sup> /h	
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	kPa / m <sup>3</sup> /h
Min. coolant flow rate / min. operation gauge pressure	m <sup>3</sup> /h / bar	/
Max. operation pressure (coolant water)	bar	/

# Technical Data Sheet

93800051112\_V01\_en\_GB

# MTU 8V4000 GS

GG08V4000A1



## Mixture cooler 1st stage, external

Coolant temperature (in / out), design		°C		
Coolant volumetric flow, design, constant <sup>13) 14)</sup>		m³/h		
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m³/h	/	
Min. coolant flow rate / min. operation gauge pressure		m³/h / bar	/	
Max. operation pressure before mixture cooler		bar		

## Mixture cooler 2nd stage, external

Coolant temperature (in / out), design		°C	43 / 44.7	
Coolant volumetric flow, design, constant <sup>13) 14)</sup>		m³/h	41.7	
Pressure drop, design <sup>14)</sup>	Cv value <sup>13) 15)</sup>	bar / m³/h	0.84	/ 46.6
Max. operation pressure before mixture cooler		bar		6

## Heating circuit interface

Engine coolant temperature (in / out), design		°C		
Heating water temperature (in / out), design		°C		
Heating water flow rate, design <sup>14) 16)</sup>		m³/h		
Pressure drop, design <sup>14)</sup>	Cv value <sup>15) 16)</sup>	bar / m³/h	/	
Max. operation gauge pressure (heating water)		bar		

## Room ventilation

Genset ventilation heat <sup>17)</sup>		kW	64	
Inlet air temperature: (min./design/max.)		°C	20 / 25 / 30	
Min. engine room temperature <sup>18)</sup>		°C	15	
Max. temperature difference ventilation air (in / out)		K	20	
Min. supply air volume flow rate (combustion + ventilation) <sup>19)</sup>		m³ / N.h	13000	

## Gearbox

Efficiency	%	100	75	50
Starter battery	%	-	-	-

## Filling quantities

Lube oil for engine		dm³	200	
Coolant in engine		dm³	135	
Coolant in mixture cooler		dm³	15	
Heating water for plate heat exchanger <sup>20)</sup>		dm³		
Lube oil for gearbox		dm³		

## Gas regulation line

Nominal size / gas pressure min. - max.		DN / mbar - mbar	80	/	120 - 250
---	--	------------------	----	---	-----------

## Engine sound level<sup>21)</sup> (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance

Frequency	Hz	63	125	250	500
Sound pressure level	dB	79.3	89.1	90.0	92.6
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	92.2	89.2	88.8	100.0
Sum of pressure levels	Lin dB	102.3			

## Sound power level

Sound power level	dB A	101.0			
Sound power level	dB	120.0			

## Undampened exhaust noise<sup>21)</sup> (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance

Frequency	Hz	63	125	250	500
Sound pressure level	dB	95.2	112.7	104.4	93.0
Frequency	Hz	1000	2000	4000	8000
Sound pressure level	dB	88.0	84.1	79.5	69.3
Sum of pressure levels	Lin dB	113.9			

## Sound power level

Sound power level	dB A	99.6			
Sound power level	dB	112.1			

## Dimensions (aggregate)

Length	mm	~ 4200		
Width	mm	~ 2000		
Height	mm	~ 2300		
Gross weight (dry weight)	kg	~ 10350 (~ 10000)		

## Power derating

Altitude		specific to the project		
Combustion air temperature		specific to the project		
Mixture cooler coolant temperature (in)		specific to the project		
Methane number		specific to the project		

## Boundary conditions and consumables

Systems and consumables have to conform to the following actual company standards:		A001067
--	--	---------

- 1) Normal cubic meter at 1013 mbar and T = 273 K
- 2) Prime power operation will be designed specific to the project
- 3) Generator gross power at nominal voltage, power factor = 1 and nominal frequency
- 4) According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- 5) Emission values during grid parallel operation
- 6) Thermal output at layout temperature; tolerance +/- 8 %
- 7) Power consumption of all electrical consumers which are mounted at the module / genset
- 8) Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- 9) Functional capability
- 10) Reference value at nominal load (without amount of oil exchange)
- 11) Genset max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- 12) Max. allowable cos phi at nominal power (view of producer)
- 13) Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary  
The system design must consider the tolerance.
- 14) Pressure loss at reference flow rate
- 15) The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- 16) Stated values for pure water, adaption for other cooling fluid composition necessary
- 17) Only generator- and surface losses
- 18) Frost-free conditions must be guaranteed
- 19) Amount of ventilation air must be adapted to the gas safety concept
- 20) Assemblies including pipe work
- 21) All sound pressure levels at nominal load
- 22) Max. admissible cos phi depending on voltage in accordance with the requirements of the BDEW Mittelspannungsrichtlinie (German Medium Voltage Directive)

EDAM / EDAT